



Arctic 1000 Series

Wide Format Professional Series

The Arctic 1040WF^c, 1064WF^c and 1064WF^t are the coolest members of the GBC color finishing line. They are designed to protect and enhance heat-sensitive media. The Arctic 1040WF^c handles films and adhesives up to 0,965 m wide, while The Arctic 1064WF^c laminates and mounts with pressure-sensitive films and adhesives up to 1,55 m wide. The 1064WF^t offers as additional feature a top-heated roller up to 50°C to reduce initial silvering. Production level speeds allow you to finish prints quickly and easily. Use with the GBC Arctic pressure-sensitive line of films and see how "cool" your prints can be!

ARCTIC 1064WF^c /
ARCTIC 1064WF^t



ARCTIC 1040WF^c

Features and Benefits

Easy To Use & Versatile

- Convenient motor-driven rewind for release liner, with brake adjustment.
- Adjustable speed for operator comfort.
- Removable front feed table facilitates changing film rolls.
- Foot pedal allows hands-free operation (not applicable for GBC 1040WF^c).
- Stand rolls easily for maximum mobility.
- Print baskets catch output and store film (not applicable for GBC 1040WF^c).
- Reversible motor clears feed jams.
- Roller gap adjusts up to 1,27 cm for mounting.



Arctic 1064 features heavy-duty core chucks.

Safety

- A disruption of the photo beam stops the rollers to protect fingers from getting caught.
- An emergency stop button is conveniently located to quickly stop the laminator and provide maximum operator control.

Superior Quality

- Large diameter, easy-to-clean silicone rollers provide a high degree of pressure to create clear output.
- Heavy-duty supply shaft reduces roll deflection (not applicable for GBC 1040WF^c).

Specifications

Core diameter:	7,62 cm
Unwind/rewind:	2 unrolls, 1 rewind
Maximum film width:	Arctic 1040WF ^o : 96,5 cm Arctic 1064WF ^o : 155 cm Arctic 1064WF ^t : 155 cm
Maximum film diameter:	15,2 OD
Material thickness:	Up to 1,27 cm
Maximum speed:	Arctic 1040WF ^o : 3,65 m/min Arctic 1064WF ^o : 5 m/min Arctic 1064WF ^t : 5 m/min
Power requirements:	220V, 10 amp, 50Hz
Dimensions (WxHxD):	Arctic 1040WF ^o : 137,1 cm x 55,8 cm x 54,6 cm Arctic 1064WF ^o : 182,8 cm x 121,9 cm x 67,3 cm Arctic 1064WF ^t : 182,8 cm x 121,9 cm x 67,3 cm
Weight:	Arctic 1040WF ^o : 74,8 kg Arctic 1064WF ^o : 129,2 kg Arctic 1064WF ^t : 128 kg
Safety:	CE Listed

Films

Arctic[®] Pressure Sensitive Laminates
Arctic[®] Mounting Adhesives



Applications



> Window Graphics



> Rigid Displays



> Banners



> POP Displays

Authorised Hybrid Reseller:

Mimaki is exclusively distributed in the UK & Ireland by:

Hybrid Services Ltd

N° 3, Gateway, Crewe, Cheshire. CW1 6YY

01270 501 900

www.hybridservices.co.uk

hybrid

Mimaki Exclusive Distributors