

# Be 'Green' thanks to the New MACtac ECO Friendly products

- Media**
- IMAGin WB inkjet- JT 1000 series**
- JT 1428 SP** white matt PP base emulsion semi-permanent acrylic adhesive
  - JT 5422 P** white glossy PP base emulsion permanent acrylic adhesive
  - JT 5499 R** transparent glossy PET base optically clear removable adhesive
- Laminates**
- PG 7400 series**
- PERMACOLOR PG 7494** satin PP film
  - PERMACOLOR PG 7498** matt PP film
  - PERMACOLOR PG 7499** gloss PP film
- IMAGin eco- mild – UV – Latex inkjet- JT 5400 series**

100% chlorine-free self-adhesive films with emulsion acrylic adhesive. These adhesives are real alternatives to traditional solvent based adhesives.

## Eco-awareness can help us all to reduce our environmental footprint!

MACtac views environmental responsibility as an integral part of good corporate citizenship and essential consideration in the products we manufacture, the processes we employ and the research and development activities that we carry out. Our products and packaging are constantly adapted to be easily recycled with up-to-date recycling techniques. MACtac has developed a comprehensive range of products which contributes to protect the environment.

## MACtac Application Accessories



## Architectural graphics

| Printing media          | Description  | Application  | Outdoor durability of the unprinted film |
|-------------------------|--|--|--|
| WW 100                  | White gloss vinyl, 55µm for wall wraps             | Interior / Exterior 3D brickwalls  | 24 months                                |
| WW 200                  | White matt, vinyl, 150µm for wall posters          | Interior decoration on flat painted walls                                    | not recommended                          |
| <b>NEW</b> WW 300       | White matt vinyl, 100µm for flat walls             | interior/exterior on difficult substrates including latex painted flat walls | 4 years                                  |
| <b>NEW</b> Deco-Texture | White matt, paper backed vinyl wall covering       | Self adhesive wall covering  | indoor use only                          |
| StreetRap               | White matt vinyl, 85µm for exterior floor graphics | Exterior Floor Graphics  | 3 months                                 |

| Laminates                             | Description  | Application  | Outdoor durability |
|---------------------------------------|--|--|--------------------|
| PG7036-75-92                          | Gloss clear PET film, 36-75-175µm                            | Anti-graffiti protection for 2D (flat) application         | 3 years            |
| <b>NEW</b> LAG 100                    | Satin clear highly conformable polymer, 60µm                 | Anti-graffiti protection for WW100 or any 3D application   | 3 years            |
| <b>NEW</b> Permafun Crystal Gloss     | Ultra clear glossy sparkling cast vinyl, 60µm                | Structured laminate for interior decoration and car tuning | 5 years            |
| <b>NEW</b> Permafun Brushed Metal     | Satin brushed texture, clear polymeric vinyl 100µm           | Structured laminate for interior decoration and car tuning | 5 years            |
| <b>NEW</b> Permafun Leather           | Satin leather texture, clear polymeric vinyl 100µm           | Structured laminate for interior decoration and car tuning | 5 years            |
| <b>NEW</b> Permafun Coarse Grain Wood | Satin coarse grain wood texture, clear polymeric vinyl 120µm | Structured laminate for interior decoration and car tuning | 5 years            |
| <b>NEW</b> Permafun Fine Grain Wood   | Satin fine grain wood texture, clear polymeric vinyl 100µm   | Structured laminate for interior decoration and car tuning | 5 years            |
| StreetRap Protect                     | Matt sand textured PVC film, 125µm                           | Laminate for exterior Floor Graphics                       | 3 months           |

## Mounting Films

| REF      | MAIN CHARACTERISTICS & APPLICATIONS   | CARRIER FILM          | ADHESIVE LAYER  | LINER   | Adhesive compatibility vs substrates |           |              |               |                        |
|----------|---|-----------------------|---|---|--------------------------------------|-----------|--------------|---------------|------------------------|
|          |   |                       |   |   | Foam PVC                             | Rigid PVC | Metacrylates | Polycarbonate | Thermocoated aluminium |
| PP 2011+ | Multi purpose, indoor/outdoor, on many substrates ; highly stable on PVC substrates | 12µm, Clear PET       | Permanent acrylic adhesive, high cohesion                                     | 90 g/m <sup>2</sup> . Supercalendered paper. MACtac grey backprinting | ++                                   | +++       | +++          | +++           | +++                    |
| PP 2012+ | Extra large mounting film for general purpose, indoor applications                  | 12µm, Clear PET       | Permanent acrylic adhesive, high performance on apolar substrates, PC, PE,... | 90 g/m <sup>2</sup> . Supercalendered paper on both sides. Unprinted  | ++                                   | ++        | ++           | +++           | ++                     |
| PP 2013+ | Indoor applications, large format High performance on difficult substrates          | 12µm, Clear PET       | Permanent rubber based high cohesion adhesive                                 | 90 g/m <sup>2</sup> Supercalendered paper. Unprinted                  | ++                                   | +++       | +++          | +++           | ++                     |
| PP 2018+ | General purpose, indoor applications  | 12µm, Clear PET       | Permanent acrylic adhesive, high performance on apolar substrates, PE,...     | 90 g/m <sup>2</sup> Supercalendered paper. Unprinted                  | ++                                   | ++        | ++           | +++           | ++                     |
| PT 2113  | Highly transparent for optically clear applications                                 | 36µm, Ultra Clear PET | Permanent solvent acrylic adhesive.   | 36µm, Clear PET on both sides.  | na                                   | na        | na           | na            | na                     |

Shelf life : 2 years / Working T° : > 5 °C and < 40 °C

## Product Overview

**IMAGin®**  
**PERMACOLOR®**



## Digital Imaging Media Laminating & Mounting Films for Wide Format Printing

Peacock issue 2



2791-FL-09-10



## MACtac® Worldwide Locations

### MACtac NORTH AMERICA

Tel.: +1-330-688-1111  
Fax: +1-330-688-2540  
E-mail: [MACtac.americas@bemis.com](mailto:MACtac.americas@bemis.com)  
[www.MACTac.com](http://www.MACTac.com)

### MACtac Mexico

Tel.: +52-444-799-0303  
Fax: +52-444-799-0309  
E-mail: [nmaceda@bemis.com](mailto:nmaceda@bemis.com)

### MACtac EUROPE

Boulevard Kennedy  
B-7060 Soignies - Belgium  
Tel : +32 (0) 67-346 211  
Fax : +32(0)67-330 574  
[MACtac.europe@bemis.com](mailto:MACtac.europe@bemis.com)  
[www.MACTac.eu](http://www.MACTac.eu)

### MACtac Australia/NZ

Tel. : +64 (0)9 920 6057  
Fax : +64 (0)9 523 6863  
E-mail: [info@mactac.co.nz](mailto:info@mactac.co.nz)

### MACtac HUNGARY

Tel.: + 36-(1)-225 1814  
Fax: + 36-(1)-225 3793  
E-mail: [info@mactac.hungary@bemis.com](mailto:info@mactac.hungary@bemis.com)

### MACtac BENELUX

Tel.: +32 (0) 67-346 211  
Fax: +32 (0) 67-346 346  
E-mail: [MACtac.europe@bemis.com](mailto:MACtac.europe@bemis.com)

### MACtac ITALIA

Tel.: +39 02-353 71 81  
Fax: +39 02-353 718 41  
E-mail: [MACtac.italy@bemis.com](mailto:MACtac.italy@bemis.com)

### MACtac CZECH REPUBLIC

Tel.: +420 (0) 224 240 700  
Fax: +420 (0) 224 210 354  
E-mail: [MACtac.czech@bemis.com](mailto:MACtac.czech@bemis.com)

### MACtac POLSKA

Tel.: +48 22/721 75 80  
Fax: +48 22/721 75 81  
E-mail: [MACtac.poland@bemis.com](mailto:MACtac.poland@bemis.com)

### MACtac DEUTSCHLAND

Tel.: +49 (0) 221-597 89 0  
Fax: +49 (0) 221-597 89 10  
E-mail: [MACtac.germany@bemis.com](mailto:MACtac.germany@bemis.com)

### MACtac SCANDINAVIA AB

Tel.: +46 (0) 40-680 31 30  
Fax: +46 (0) 40-680 31 39  
E-mail: [MACtac.scandinavia@bemis.com](mailto:MACtac.scandinavia@bemis.com)

### MACtac ESPAÑA

Tel.: +34.90.215 7994  
Fax: +34.93.335 0100  
E-mail: [MACtac.spain@bemis.com](mailto:MACtac.spain@bemis.com)

### MACtac SCHWEIZ

Tel.: +41 (0) 52-720 80 00  
Fax: +41 (0) 52-720 70 14  
E-mail: [MACtac.ch@bluewin.ch](mailto:MACtac.ch@bluewin.ch)

### MACtac FRANCE

Tel.: +33 (0)1 64 54 78 00  
Fax: +33 (0)1 69 34 54 15  
E-mail: [MACtac.france@bemis.com](mailto:MACtac.france@bemis.com)

### MACtac U.K.

Tel.: +44 (0)1604-644 697  
Fax: +44 (0)1604-75 790 495  
E-mail: [MACtac.uk@bemis.com](mailto:MACtac.uk@bemis.com)

## MACtac ASIA PACIFIC

### MACtac SINGAPORE

Tel: +65-6741 3088  
Fax: +65-6741 5088  
E-mail: [MACtac.Asia@bemis.com](mailto:MACtac.Asia@bemis.com)

### MACtac SHANGHAI CHINA

Tel. +86-021-50589370  
Fax: +86-021-50589375  
E-mail: [sales@mactac-china.com](mailto:sales@mactac-china.com)

YOUR STOCKIST

© Registered Trademark of Morgan Adhesives Company.

Note : all data published in this brochure are intended only as a source of information and are therefore given without guarantee. Additionally, purchasers are advised that they should determine, by independent testing, the suitability of MACtac materials for their intended use. For more technical information, please refer to the Technical Data Sheets for the products described in this brochure.

P E R F O R M A N C E G R A P H I C S

IMAGin® MACmark® PERMACOLOR® MACscreen®

# Digital Imaging Media for Wide Format Printing

# Laminating Films

| Printing media  | Description   | Adhesive   | Liner                         | Outdoor durability of the unprinted film | Laminates          | Description  | Adhesive                     | Liner                                  | Outdoor durability |
|---|---|--|-------------------------------|--|--------------------|--|------------------------------|--|--------------------|
| <b>Budget Films for Flat surfaces, short term outdoor or indoor applications</b>  |   |  |                               |  |                    |  |                              |  |                    |
| Printvinyl 828-29 P/R - 899 R   | White gloss/matt/clear vinyl, 80µm                  | Permanent or Removable, clear acrylic                    | Coated Kraft Liner, 120g/m²   | 2 years                                  | Printcover 898-899 | Matt / gloss clear calendered PVC 70 µm                      | Clear acrylic adhesive       | Coated kraft liner, 120g/m²            | 2 years            |
| <b>Flat surfaces, short to medium term outdoor or indoor applications</b>         |   |  |                               |  |                    |  |                              |  |                    |
| JT 5822-24 P / R  | White gloss/matt vinyl, 100µm                       | Permanent or Removable, clear acrylic                    | Coated Kraft Liner, 120g/m²   | 3 years                                  | LF 3894            | Semi-matt clear calendered PVC film, 80µm                    | Clear acrylic adhesive       | Supercalendered white paper, 80g/m²    | 3 years            |
| JT 5122 P / R   | White gloss vinyl, 100µm                            | Permanent or Removable, opaque (grey) acrylic            | Coated Kraft liner 120g/m²    | 3 years                                  | LF 3898 - LUV 3898 | Matt clear calendered PVC film, 80µm                         |                              |  |                    |
| JT 5829 SPB   | White gloss vinyl, 100µm                            | Semi-Permanent opaque (black) acrylic                    | Coated Kraft liner 120g/m²    | 3 years                                  | LF 3899 - LUV 3899 | Gloss clear calendered PVC film, 80µm                        |                              |  |                    |
| JT 5828-29 P / R (*1)   | White matt/gloss vinyl, 100µm                       | Permanent or Removable, opaque (grey) solvent acrylic    | Coated Kraft Liner, 140g/m²   | 4 years                                  | PG 7281            | Gloss clear monomeric PVC film, 80µm                         |                              |  |                    |
| JT 5829 MBF   | White gloss vinyl, 100µm                            | Micro-structured Permanent opaque (grey) solvent acrylic | PE coated Liner, 130g/m²      | 4 years                                  | PG 7284            | Satin clear monomeric PVC film, 70µm                         |                              |  |                    |
|   |   |  |                               | 4 years                                  | PG 7285-86         | Matt clear monomeric PVC film, 70µm                          |                              | Supercalendered yellow paper, 90g/m²   | 4 years            |
|   |   |  |                               | 4 years                                  | PG 7291            | Matt clear monomeric PVC film, 200µm                         |                              | Supercalendered yellow paper, 90g/m²   | 4 years            |
|   |   |  |                               | 4 years                                  |                    |  |                              | Clear PET, 36 µm                       | not suitable       |
| JT 5422 P   | White semi-gloss PVC free film, 100µm               | Permanent opaque (grey) acrylic                          | Coated Kraft liner, 140g/m²   | 2 years                                  | PG 7034            | Gloss clear PP, 30µm   | Clear acrylic adhesive       | Clear PET, 36 µm                       | not suitable       |
|   |   |  |                               | 2 years                                  | PG 7494-98-99      | Satin-matt-gloss PP film, 80µm                               |                              | White coated kraft liner, 100g/m²      | 2 years            |
| <b>Flat or simple curved surfaces (convex), long term outdoor applications</b>    |   |  |                               |  |                    |  |                              |  |                    |
| JT 5928-29 P (*1)   | White matt/gloss vinyl, 70µm                        | Permanent opaque (grey) acrylic                          | Coated Kraft Liner, 140g/m²   | 7 years                                  | LF 3998 - LUV 3998 | Matt clear stabilized PVC film, 80µm                         | Clear acrylic adhesive       | White clay coated Kraft paper, 140g/m² | 5 years            |
| JT 5929 MBF   | White gloss vinyl, 70µm                             | Micro-structured Permanent opaque (grey) acrylic         | PE coated Liner, 130g/m²      | 7 years                                  | LF 3999 - LUV 3999 | Gloss clear stabilized PVC film, 80µm                        |                              |  |                    |
| <b>Vehicle wrapping and Decoration (convex and concave)</b>                       |   |  |                               |  |                    |  |                              |  |                    |
| JT 5529 P (*1)  | White gloss, highly conformable vinyl, 55µm         | Permanent opaque (grey) acrylic                          | Coated Kraft Liner, 140g/m²   | 10 years                                 | LF 3398            | Matt highly conformable cast PVC film, 30 µm                 | Clear acrylic adhesive       | Clear PET, 30µm                        | 4 years            |
| JT 5529 MBF   | White gloss, highly conformable vinyl, 55µm         | Micro-structured Permanent opaque (grey) acrylic         | PE coated Liner, 130g/m²      | 10 years                                 | LUV 3399           | Ultra-clear gloss highly conformable cast PVC film, 30µm     |                              |  |                    |
| JT 5599 P   | Gloss clear, highly conformable vinyl, 55µm         | Permanent clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 8 years                                  | LF 3499            | Ultra-clear gloss highly conformable cast PVC film, 40µm     |                              |  |                    |
| JT 5629 PM  | White gloss cast PVC film, 50µm                     | Permanent opaque (grey) acrylic                          | PE coated Liner, 130g/m²      | 7 years                                  |                    |  |                              |  |                    |
|   |   |  |                               | 7 years                                  |                    |  |                              | Coated Kraft paper, 130g/m²            |                    |
|   |   |  |                               | 7 years                                  |                    |  |                              | Clay coated paper, 120g/m²             |                    |
| <b>One-way vision window films</b>  |   |  |                               |  |                    |  |                              |  |                    |
| JT 5915 P   | 50 % Perforated (1.5mm) window film, 200µm          | Semi-Permanent clear acrylic                             | Perforated PE Liner, 160g/m²  | 2 years                                  | LF 3697            | Ultra-clear very conformable cast PVC film, 50µm             | Ultra-clear acrylic adhesive | Matt PET film, 36µm                    | 5 years            |
| JT 5817 P   | 45 % Perforated (1.6mm) window film, 160µm          | Semi-Permanent clear acrylic                             | Solid PE liner, 135g/m²       | 1 year                                   | PG 7036            | Gloss clear PET film, 36µm (flat surfaces, anti-graffiti)    | Clear acrylic adhesive       | Clear PET, 36µm                        | 3 years            |
| JT 5837 P   | 30 % Perforated (1.5mm) window film, 160µm          | Semi-Permanent clear acrylic                             | Solid PE liner, 135g/m²       | 1 year                                   |                    |  |                              |  |                    |
| <b>Pastitized banner markings, escalator handrails, rubber belts supermarkets</b> |   |  |                               |  |                    |  |                              |  |                    |
| JT 5826 P   | White matt very soft vinyl, 70µm                    | Permanent clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 3 years                                  | none               |  |                              |  |                    |
| <b>Illuminated signs</b>  |   |  |                               |  |                    |  |                              |  |                    |
| JT 5728 P   | Translucent white matt vinyl, 80µm. Polymeric.      | Permanent clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 7 years                                  | LF 3900 series     | Gloss or Matt clear stabilized PVC film, 80µm                | Clear acrylic adhesive       | White clay coated Kraft paper, 140g/m² | 5 years            |
| JT 5827 P   | Translucent white gloss vinyl 80µm. Monomeric.      | Permanent clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 2 years                                  | LF 3800 series     | Gloss, semi-matt or matt clear calendered PVC film, 80µm     | Clear acrylic adhesive       | Supercalendered white paper, 80g/m     | 3 years            |
|   |   |  |                               |  | PG 7200 series     | See above (Flat surfaces, short to medium term applications) |                              |  |                    |
| <b>Architectural graphics</b>   |   |  |                               |  |                    |  |                              |  |                    |
| WW 100  | White gloss vinyl, 55µm for wall wraps.             | High tack permanent opaque (grey) acrylic                | PE coated Liner, 130g/m²      | 24 months                                | LAG 100            | Satin clear highly conformable polymer, 60µm                 | Clear acrylic adhesive       | White clay coated Kraft paper, 135g/m² | 3 years            |
| WW 200  | White matt, vinyl, 150µm for wall posters.          | Removable and repositionable clear acrylic               | PE coated liner, 160g/m²      | not recommended                          | LUV 3399           | Ultra-clear gloss highly conformable cast PVC film, 30µm     |                              |  |                    |
| WW 300  | White matt vinyl, 100µm                             | High tack Permanent opaque acrylic                       | Coated Kraft Liner, 140g/m²   | 4 years                                  | LF 3398            | Clear matt highly conformable cast PVC film, 30µm            |                              |  |                    |
| Deco-Texture  | White matt, paper backed vinyl wall covering        | Permanent clear acrylic, removable by steaming           | Coated Kraft Liner, 120g/m²   | indoor use only                          | LF 3800            | Gloss, semi-matt or matt clear calendered PVC film, 80µm     | Clear acrylic adhesive       | Supercalendered white paper, 80g/m²    | 3 years            |
|   |   |  |                               |  | LUV 3800 series    | See above (Flat surfaces, short to medium term applications) |                              |  |                    |
|   |   |  |                               |  | PG 7200 series     |  |                              |  |                    |
| <b>Decorations on glass surfaces</b>  |   |  |                               |  |                    |  |                              |  |                    |
| JT 5899 R (*1)  | Gloss clear vinyl, 100µm. Monomeric.                | Removable clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 3 years                                  | LF 3800            | Gloss, semi-matt or matt clear calendered PVC film, 80µm     | Clear acrylic adhesive       | Supercalendered white paper, 80g/m²    | 3 years            |
| JT 5999 R   | Gloss clear vinyl, 80µm. Polymeric.                 | Removable clear acrylic                                  | Coated Kraft Liner, 140g/m²   | 5 years                                  | LF 3900 series     | Gloss or Matt clear stabilized PVC film, 80µm                | Clear acrylic adhesive       | White clay coated Kraft paper, 140g/m² | 5 years            |
| JT 5999 MBF   | Gloss clear vinyl, 80µm. Polymeric.                 | Micro-structured Permanent clear acrylic                 | PE coated Liner, 130g/m²      | 5 years                                  |                    |  |                              |  |                    |
| JT 5796 MBF   | Translucent matt etched vinyl, 80µm                 | Micro-structured Permanent clear acrylic                 | PE coated Liner, 130g/m²      | 5 years                                  | none               |  |                              |  |                    |
| JT 5798 MBF   | Translucent matt dusted vinyl, 80µm                 | Micro-structured Permanent clear acrylic                 | PE coated Liner, 130g/m²      | 5 years                                  | none               |  |                              |  |                    |
| JT 5499 R   | Optically clear PET film, 75µm                      | Removable clear acrylic                                  | Polyester release liner, 25µm | 1 year (indoor)                          | LF 3697            | Ultra-clear very conformable cast PVC film, 50µm             | Ultra-clear acrylic adhesive | Matt PET film, 36µm                    | 5 years            |
|   |   |  |                               |  | PG 7036            | Gloss clear PET film, 36µm (flat surfaces, anti-graffiti)    | Clear acrylic adhesive       | Clear PET, 36 µm                       | 3 years            |
| <b>Floor Graphics</b>   |   |  |                               |  |                    |  |                              |  |                    |
| JT 5829 R/P   | White gloss vinyl, 100µm                            | Permanent or Removable, clear acrylic                    | Coated Kraft Liner, 120g/m²   | 3 years                                  | PF 6200            | Grain textured Polycarbonate film, 125µm                     | Clear acrylic adhesive       | Clear PET, 36µm                        | 9 months           |
| JT5822 R/P  | White gloss vinyl, 100µm                            | Permanent or Removable, opaque (grey) solvent acrylic    | Coated Kraft Liner, 140g/m²   | 4 years                                  | PF 6300            | Grain textured PVC film, 125µm                               |                              |  |                    |
|   |   |  |                               |  | PF 6301            | Semi matt sandy structured PVC film, 100µm                   |                              |  |                    |
|   |   |  |                               |  | PF 6400            | Grain textured Polypropylene film, 125µm                     |                              |  |                    |
| StreetRap   | White matt vinyl, 85µm for exterior floor graphics. | Permanent aggressive clear acrylic                       | PE coated liner, 160g/m²      | 3 months                                 | StreetRap Protect  | Matt sand textured PVC film, 125µm                           | Clear acrylic adhesive       | Supercalendered yellow paper, 90g/m²   | 3 months outdoor   |




(\*1) also available with a PE coated Liner

ICC profiles at [www.mactac.eu](http://www.mactac.eu) Water Based printing media also available for dye and pigmented inks : see [www.mactac.eu](http://www.mactac.eu)

Remark: Technical Data Sheets on all products are available in the PDF format on [www.mactac.eu](http://www.mactac.eu)

MACTac denies responsibility for product failure if non-MACTac laminating films are used for the application.

# Application Guide

| Media  | Laminates   |
|--|---|
|  <b>FLAT</b><br>Signs, Flat vehicle graphics, Building signage, POS, Sandwich boards, etc                   | Printvinyl 828-29-99<br>JT 5822-24 P/R<br>JT 5122 P/R<br>JT 5828-29 P/R/PM/RM<br>JT 5829 MBF<br>JT 5422 P   |
|  <b>SLIGHT CURVES</b><br>Vehicle graphics (convex curves only),   | JT 5928-29 P/PM longterm<br>JT 5929 MBF   |
|  <b>DIFFICULT CURVES, CORRUGATIONS RIVETS</b><br>Vehicle graphics, Full body wraps, corrugations, curves    | JT 5529 P/PM<br>JT 5529 MBF<br>JT 5599 P<br>JT 5629 PM  |
|  <b>BACKLIT</b><br>Illuminated signage  | JT 5728 P<br>JT 5827 P  |
|  <b>BANNER</b><br>Banners, Sails, Escalator handrails, Supermarket rubber belts                             | JT 5826 P   |
|  <b>GLASS</b><br>Window decorations<br>One-way-vision applications  | JT 5899 (R/RM)<br>JT 5798 MBF (dusted effect)<br>JT 5796 MBF (etched effect)<br>JT 5999 MBF (gloss clear)<br>JT 5915 P (mobile advertising)<br>JT 5817-37 P (promotional grade)<br>JT 5999 R<br>JT 5499 R |
|  <b>FLOOR GRAPHICS (interior use)</b><br>Floor graphics, Stairs and table tops. (with recommended laminate) | JT 5822 P/R<br>JT 5829 P/R/PM/RM  |
|  <b>FLOOR GRAPHICS (exterior use)</b><br>Exterior Floor graphics and Stairs<br>Promotion outdoors          | StreetRap<br>StreetRap Protect  |
|  <b>WALL GRAPHICS ON BRICKS</b><br>Direct application on bricks   | WW 100<br>LF 3398/LUV 3399<br>LAG 100   |
|  <b>INTERIOR WALL GRAPHICS</b><br>Direct application on smooth, flat surface                              | JT 5829 P / JT 5829 PM<br>JT 5929 P / PM<br>WW300 (painted walls)<br>WW200<br>Deco-Texture  |
|  <b>MOBILE ADVERTISING (short/medium term)</b><br>Flat vehicle graphics                                   | JT 5829 SPB<br>JT 5829 R<br>JT 5822 R<br>JT 5829 R<br>JT 5122 R   |